



EXODISP C 7301

Chemical description: Styrene Acrylic copolymer

Free of plasticizer and solvent is stabilised by means of a biodegradable system

Characteristics: EXODISP C 7301 shows excellent pigment/extender wetting properties

Specifications:	Solid content	49.0 - 51.0 %	EOC method: 2016
	pH	7.0 - 8.0	EOC method: 3001
	Viscosity 4/20 cps	1500-6000	EOC method: 73017

Dispersion properties:	Appearance	White, emulsion
	Polymer Type	Styrene Acrylic
	Emulsifying system	Anionic (biodegradable)
	Particale size	Ca.120 nm

Film properties:	Appearance	Clear, glossy and transparent
	Surface	Non tacky
	TG	+18°C
	MFFT	+17°C

note: All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefor. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

EOC Polymers India Pvt. Ltd - Registered Office: A-220, Defence Colony, New Delhi, India, 110024
Site 1 : Plot No. 474A & 474B, HSIIDC, Industrial Estate, Phase 1 Barhi, Dist. Sonapat, Haryana, India -131101
Site 2 : Plot No. 833, GIDC Industrial Est, Jhagadia, Opp. Gujarat Gas, Near Getco Substation, Dist. Bharuch, Gujarat India - 393110,
Phone : +91 130 247 47 31 - Fax: +91 130 247 47 32
info@eocgroup.com www.eocgroup.com



EOC India- Emulsion Division

Application: EXODISP C 7301 has good film forming and binding properties, with excellent resistance towards alkalis and water. The product can be used for interior and exterior paints with good washability, it is also suitable for the formulation of floortile and building adhesives, roof coatings and sealants.

Storage: In shade of the sun and at temperatures between +5°C and +40°C.

Shelf life: 6 months in original closed packaging.

note: All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefor. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

EOC Polymers India Pvt. Ltd - Registered Office: A-220, Defence Colony, New Delhi, India, 110024
Site 1 : Plot No. 474A & 474B, HSIIDC, Industrial Estate, Phase 1 Barhi, Dist. Sonapat, Haryana, India -131101
Site 2 : Plot No. 833, GIDC Industrial Est, Jhagadia, Opp. Gujarat Gas, Near Getco Substation, Dist. Bharuch, Gujarat India - 393110,
Phone : +91 130 247 47 31 - Fax: +91 130 247 47 32
info@eocgroup.com www.eocgroup.com