

EOC Polymers India Pvt. Ltd.

CIN: U25199DL2006FTC145680

Date of issue: 15/02/19

Exodisp D 4010

Chemical description: Sodium polyacrylate

Characteristics: It produces compounds with:

low viscosity

small particle size

ameliorated viscostability

Specifications: Solid content 45.0 +/- 1.0 % EOC method: 2016

pH 7.0-7.6 EOC method: 3001 Viscosity < 2000 mPa.s EOC method: 73011

Dispersion properties: Appearance Colourless to yellow liquid

Molecular weight Ca. 4500 Dalton

Applications: Exodisp D 4010 is used as a dispersant

Storage: In shade of the sun and at temperatures between +18°C and

+30°C.It is important to have a storage temperature of +18°C in

order to prevent crystallization.

Shelf life: 6 months in original closed packaging

Note: All recommendations for use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge at the time such recommendations are made. As additional information is learned, these recommendations may be updated. They may also be impacted by circumstances outside our control. Notwithstanding any such recommendations, the user shall remain responsible for satisfying himself that the product as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefor. The user shall ensure that the intended use of the products will not infringe any third party's intellectual property rights.

EOC Polymers India Pvt. Ltd - Registered Office: 2nd Floor,AB-03,Safdarjung Enclave, New Delhi, India, 110029 Site 1: Plot No. 474A & 474B, HSIIDC, Industrial Estate, Phase 1 Barhi, Dist. Sonepat, Haryana, India -131101 Site 2: Plot No. 833, GIDC Industrial Est, Jhagadia, Opp. Gujarat Gas, Near Getco Substation, Dist. Bharuch, Gujarat India - 393110,

Phone: +91 130 247 47 31 - Fax: +91 130 247 47 32

info@eocgroup.com www.eocgroup.com